



C
E
R
T
I
F
I
C
A
T
E



Certificate number: 2501712 (2)

Issued 08/01/2025
Expires 06/01/2030

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)
Model number(s) – see Appendix

Commercial Hot Water Solutions Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009
Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Commercial Hot Water Solutions Ltd
71-72 Gazelle Road
Weston Industrial Estate
Weston-super-Mare
Somerset
BS24 9ES
United Kingdom



KUKreg4

Product Certificate

Appendix to Certificate number: 2501712

The following products belong to this certificate

| |
|--|
| PRODUCT DESCRIPTION |
| Range of hot water buffer tanks consisting of stainless steel shells for potable water. |
| ATS3 – Without Production Surveillance. |
| MODEL(S) |
| XMF 200 Litre |
| XMF 300 Litre |
| XMF 500 Litre |
| XMF 800 Litre |
| XMF 1000 Litre |
| XMF 1500 Litre |
| XMF 2000 Litre |
| XMF 2500 Litre |
| SIZE: |
| 2" BSP (F), |
| 2 1/2" BSP (F). |
| SCOPE: |
| Manufacturer recommended maximum working pressure 6.0 Bar & maximum operating temperature 95°C. |
| Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C. |
| MARKING |
| CHWS logo, website, model no, material, capacity, temperature, pressure, manufacturing date (YYYY/WW) and other technical information on data label on body. |
| MATERIALS |
| Non-metallic materials assessed (BS6920) to point of discharge. |
| BACKFLOW PROTECTION NOTES |
| N/A. |
| ADDITIONAL NOTES |
| All water contact & exposed components satisfy opacity requirements. |

Extra Notes